

Product Specification: LI-ION-18650-3200MAH-3.6V

3200mAh 3.6V 18650 Lithium-Ion Cell

1. Scope

This product specification has been prepared to specify the rechargeable Lithium-ion Polymer cell ('cell').

2. Description and Model

2.1 Description Cell (lithium-ion rechargeable cell)

2.2 Model Li-Ion-18650-3200mAh-3.6V

3. Specifications

1	Charge Voltage	DC: 4.2V	
2	Nominal Voltage	3.6V	
3	Minimal Capacity	3000mAh @0.2C Discharge	
4	Charge Current	Standard charge: 0.5C	
5	Standard Charging Method	0.5C CC (constant current) charge to 4.2V, then CV (constant voltage 4.2V) charge until charge current declines to 0.01C.	
6	Charging Time	Standard charge: 2 hours	
7	Max. Charge Current	1C	
8	Max. Discharge Current	2C	
9	Discharge Cut-off Voltage	2.5V	
10	Operating Temperature	Charging: 0 to 45°C	Discharging: -20 to 60°C
11	Storage Temperature	0C ~ to 60°C	
12	Battery Weight	Approx. 45g	
13	Battery Dimensions	Length: 64.9 ± 0.3mm	Diameter: 18.4 ± 0.2mm

4. Battery Performance Criteria

4.1 Electrical Characteristics

	Item	Test Method & Condition	Criteria
1	Standard Charge	Charging the battery initially with constant current at 0.5C and then with constant voltage at 4.2V until charge current declines to 0.01C.	N/A
2	Initial Capacity	The capacity means the discharge capacity of the battery, which is measured in terms of discharge current of 0.2V and 2.5V cut-off voltage after the standard charge.	≥ 3000mAh
3	Cell Cycle Life	Test condition: Charge: 0.5C to 4.2V Discharge: 1C to 2.5V 80% or more of 1st cycle capacity at 1C discharge of Operation	≥ 500 cycles
4	Self-Discharge	After the standard charging, store the battery under the condition as No. 4.4 for 30 days, then measured the capacity with 0.2V until 2.5V.	Remaining Capacity > 90%

Product Specification: LI-ION-18650-3200MAH-3.6V

3200mAh 3.6V 18650 Lithium-Ion Cell

5	Initial Impedance	Internal resistance measured at AC 1KHz after 50% charge.	$\leq 35\text{m}\Omega$
6	Battery Voltage	As of shipment.	3.6V - 3.8V

4.2 Mechanical Characteristics

	Item	Test Method & Condition	Criteria
1	Vibration Test	After standard charging, fixed the battery to vibration table and subjected to vibration cycling that the frequency is to be varied at the rate of 1Hz per minute between 10Hz an 55Hz, the amplitude of the vibration is 1.6mm. The battery shall be vibrated for 30 minutes towards per axis of XYZ axes.	No fire or leakage.
2	Drop Test	The battery is to be dropped from a height of 1 meter twice onto concrete ground.	No fire, explosion or leakage.

4.3 Visual Inspection

There shall be no such defects as scratch, flaw, crack, and leakage which may adversely affect commercial value of the cell.

4.4 Standard Environmental Test Conditions

Unless otherwise specified, all tests stated in this Product Specification are conducted at the condition below:

Temperature : $23 \pm 5^\circ\text{C}$

Humidity : $65 \pm 20\% \text{ RH}$

5. Storage and Others

5.1 Long Time Storage

If the Battery is stored for a long time (over 3 months), the battery's storage voltage should be 3.6-3.8V and the Battery is to be stored in according to the condition specified about No. 4.4.

5.2 Others

Any matters that this specification does not cover should be discussed between the customer and the manufacturer.

Product Specification: LI-ION-18650-3200MAH-3.6V
3200mAh 3.6V 18650 Lithium-Ion Cell

6. Dimensions

